Counters Dual Multifunction Display Types DMF1462



DMF1462

Product Description

This multifunction display is similar to the DMF1461 but it can display 2 different functions at once. It can be used for a multitude of

applications. Can display eg.: pulse and frequency, 2 pulse counters, pulse and time, 2 timers...

Approvals



Output Type

A12

No output

Input Type

00

Standard (also fixed voltage input available upon request)

General Data

| Display | 6 digits LED type |
|-------------------------|---------------------------------|
| Dimensions of digits | H 14mm/0.55" |
| Viewing angle | Frontal |
| Colour of digit figures | Red |
| Current consumption | <50mA, 6VA |
| Data Back-up | E ² PROM |
| Operating temperature | -20+65°C/4149°F |
| Storage temperature | -25+70°C/-13158°F |
| Mounting position | Panel mounting |
| Housing colour | RAL7021 (grey) |
| Dimensions | 48x96 acc. to DIN 43700 STD |
| Weight | 150g/5.29oz |
| Panel cut-out HxL | 48x92mm / 1.89"x3.62" |
| Protection degree | IP65 (front) |
| EMC | acc. to directive 89/36/ENG |
| emitted: | EN61000-6-4 EN550011 class B |
| immunity: | EN61000-6-2 |



- Programmable function:
 - Pulse counter
 - Position display
 - Frequency/speed • Timer/time meter
- AC/DC supply
- High rate accuracy system
- DIN 48x96
- IP65 front protection

Ordering Key

DMF1462 A12 0 00

Type ______ Output ______ Supply voltage code ______ Input type ______ Stock items: DMF1462A12000 DMF1462A12300

Supply Voltage

| 0 | 90260VAC |
|---|-----------------------|
| 3 | 1030VDC (with reverse |
| | polarity protection) |

Measuring Specifications

| Time range | 0.001s999 999h |
|--------------------------------|-----------------|
| Counting Frequency | 60kHz |
| Counting system | Programmable |
| Reset time | <5ms |
| Accuracy Tachometer: Timer: | <0.1% <50ppm |

Input Specifications

| Polarity | PNP or NPN programmable |
|------------------------------------|---|
| Resistance | ~ 5kΩ |
| Switching level | |
| STD DC input version AC version | High: 0.6 x U _B Low: 0÷4VDC |
| | High: 1230VDC |

Package Content


| - | |
|---|-------------------------------------|
| 1 | Instrument DMF1462 |
| 1 | Panel mounting clip |
| 1 | Screw terminal block 2 pins RM 5.08 |
| 1 | Screw terminal block 7 pins RM 3.81 |
| 1 | Gasket |
| 1 | Multilingual operating manual |




Counters Dual Multifunction Display Types DMF1462



Block Diagram



Dimensions (mm/inches)



Connections

| | <u>1 2 3 4 5 0</u> X1 | 5 7 | | 1 2 X2 | |
|---------------|--------------------------|-------------|---------------|-------------|-------------|
| Connector X1: | | Conne | Connector X2: | | |
| Pin | AC- version | DC- version | Pin | AC- version | DC- version |
| 1 | Not connected | | 1 | 90260VAC | 0VDC (GND) |
| 2 | Not connected | | 2 | 90260VAC | 1030VDC |
| 3 | Reset | | | | |
| 4 | INP B | | | | |
| 5 | INP A | | | | |
| 6 | GNDout | n.c. | | | |
| 7 | +24 Vout | n.c. | | | |